


H31

METALIZED POLYPROPYLENE

Plastic Case



LEAD LENGTH = 1.5" MIN.



Axial Lead

Lead Gauge	67VAC / 100VDC	135VAC / 200VDC
24AWG	.001 - .47	.001 - .22
22AWG	.68 - 1.0	.33 - .82
20AWG	2.0 - 5.0	1.0 - 2.0

MFD	67 VAC / 100 VDC				135 VAC / 200 VDC			
	T +.05	W +.05	L +.05	PART NO.	T +.05	W +.05	L +.05	PART NO.
.0010	.17	.29	.42	H31B102	.17	.29	.42	H31C102
.0015	.17	.29	.42	H31B152	.17	.29	.42	H31C152
.0022	.17	.29	.42	H31B222	.17	.29	.42	H31C222
.0033	.17	.29	.42	H31B332	.17	.29	.42	H31C332
.0047	.17	.29	.42	H31B472	.17	.29	.42	H31C472
.0068	.17	.29	.42	H31B682	.17	.29	.42	H31C682
.0082	.17	.29	.42	H31B822	.17	.29	.42	H31C822
.010	.17	.29	.42	H31B103	.17	.29	.42	H31C103
.015	.17	.29	.42	H31B153	.17	.29	.55	H31C153
.022	.17	.29	.42	H31B223	.17	.29	.55	H31C223
.033	.17	.29	.55	H31B333	.17	.29	.55	H31C333
.047	.17	.29	.55	H31B473	.23	.36	.55	H31C473
.068	.17	.29	.55	H31B683	.23	.36	.55	H31C683
.082	.17	.29	.55	H31B823	.29	.42	.55	H31C823
.10	.23	.36	.55	H31B104	.29	.42	.55	H31C104
.15	.23	.36	.55	H31B154	.29	.42	.67	H31C154
.22	.29	.42	.55	H31B224	.29	.42	.82	H31C224
.33	.29	.42	.67	H31B334	.39	.54	.82	H31C334
.47	.29	.42	.82	H31B474	.39	.54	1.04	H31C474
.68	.39	.54	.82	H31B684	.39	.54	1.24	H31C684
.82	.39	.54	.82	H31B824	.39	.54	1.24	H31C824
1.0	.39	.54	1.24	H31B105	.56	.72	1.24	H31C105
2.0	.56	.72	1.24	H31B205	.56	.72	1.75	H31C205
5.0	.56	.72	1.75	H31B505				

Non Standard Values Available Upon Request

Add letter to the end of the part number to specify the tolerance.

- ±20% = M
- ±10% = K
- ±5% = J
- ±3% = H
- ±2% = G
- ±1% = F



Bishop Electronics Corporation

3729 San Gabriel River Parkway • Pico Rivera CA 90660
 (562) 695-0446 (562) 692-9391 FAX : (562) 692-4008
 email: Sales@bishopelectronics.com